


EC TYPE-EXAMINATION CERTIFICATE

according to Marine Equipment Directive (Module B)



NOTIFIED BODY 0809

This is to certify that Eurofins Expert Services Ltd did undertake the relevant type approval procedures for the type of equipment identified below which was found to be in compliance with the requirements of Marine Equipment Directive (MED) 2014/90/EU and Commission implementing regulation (EU) 2018/773 subject to any conditions in the schedule attached hereto.

DEKOSteel

meet the requirements imposed in IMO 2010 FTP Code, Annex 1 Part 2 and Part 5 (IMO Resolution MSC.307(88) Annex 1 Part 2 and Part 5) on

materials with low flame-spread characteristics and not producing excessive quantities of smoke and toxic products or not giving rise to toxic hazards at elevated temperatures

and the provisions of Marine Equipment Directive 2014/90/EU, that apply to

surface materials with low flame-spread characteristics.

These products have been assigned a U.S. Coast Guard Module B number (**164.112 / EC0809**) to note type approval to Module B only as it pertains to obtaining U.S. Coast Guard approval as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment" signed February 18th, 2019.

Manufacturer of the product is

Dekotel Coating Oy

The Certificate is valid until June 25, 2024 unless suspended, expired or withdrawn, provided the conditions in this certificate are complied with and the equipment remains satisfactory in service.

Espoo June 26, 2019

This document is electronically approved

Tiina Ala-Outinen
Business Manager

Heli Välimäki
Senior Expert

Manufacturer	Dekotel Coating Oy Hepolammentie 25, FI-08680 Lohja Finland.
Regulation Item	MED /3.18 b, surface materials with low flame-spread characteristics, paint systems.
Product description	DEKOSteel, coated steel sheet. PE-coating 50 µm + PU-coating 50 µm + water based inks. All colours.
Approved application	Thickness of metallic sheet shall be at least 0.45 mm. Used on bulkhead, wall and ceiling linings.
Technical document	Työohjeet DEKOSteel, Versio 1.1 06/2019.
Test reports	Test Report EUFI29-19001441-T1 (June 17, 2019), Eurofins Expert Services Oy, Finland.
Test methods	IMO 2010 FTP Code Annex 1 Part 2 and Part 5 (IMO Resolution MSC.307(88) Annex 1 Part 2 and Part 5).
Notes	<p>This certificate will not be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with the notified body named on this certificate.</p> <p>Should the specified regulations or standards be amended during the validity of this certificate, the product is to be reapproved prior to it being placed on board vessels to which the amended regulations or standards apply.</p> <p>The Mark of Conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-control phase module (D, E or F) of Annex B of the Directive is fully complied with and controlled by a written inspection agreement with a notified body.</p>

END OF CERTIFICATE